



MODLE NO.	BLV238	BOTTOM LOADING VALVE, 6 INCH WITH PNEUMATIC/HYDRAULIC DE-FUEL ACTUATOR INTERFACES WITH 6 INCH TTMA SUMP FLANGE AT THE TANK AND 6 INCH ANSI 150 LB. FLANGE AT DISCHARGE
OPTIONS	D	ADDS PRIMARY PILOT
	E	ADDS PRIMARY AND SECONDARY PILOTS
	M	BOTTOM LOADING VALVE, 6 INCH WITH PNEUMATIC/HYDRAULIC DE-FUEL ACTUATOR INTERFACES WITH MEGGITT SPECIAL MOUNTING FLANGE
	N	BOTTOM LOADING VALVE, 6 INCH WITH 6 INCH TTMA MOUNTING FLANGED ELBOW, 6 INCH VICTAULIC INLET AND VALVE CLOSE POSITION INDICATOR

EXAMPLE:  
 P/N BLV238 = BOTTOM LOADING VALVE, 6 INCH WITH PNEUMATIC/HYDRAULIC DE-FUEL ACTUATOR AND NO PILOT INCLUDED  
 P/N BLV238E = BOTTOM LOADING VALVE, 6 INCH WITH PNEUMATIC/HYDRAULIC DE-FUEL ACTUATOR WITH DUEL PILOTS ADDED

OPTION	ITEM NO.	PART NO.	DESCRIPTIONS	QTY
E	4	RJ1459	ORIFICE	1
E				-
D	3	RJ1234	PLUG	1
STD				2
E				2
D	2	RJA1115	PILOT	1
N		RJA1267	BOTTOM LOADING VALVE SUBASSEMBLY WITH TTMA MOUNTING FLANGED ELBOW, 6 INCH VICTAULIC INLET AND VALVE CLOSE POSITION INDICATOR	1
M	1	RJA1159	BOTTOM LOADING VALVE SUBASSEMBLY WITH MEGGITT F620 FLANGE	1
STD		RJA1158	BOTTOM LOADING VALVE SUBASSEMBLY WITH TTMA FLANGE	

PROPRIETARY AND CONFIDENTIAL  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF...  
 REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF... IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME	DATE
DIMENSIONS ARE IN INCHES		DRAWN	
FRACTIONAL: ±		CHECKED	
ANGULAR: ± MACH ± BEND ±		ENG APPR.	
TWO PLACE DECIMAL: ±		MFG APPR.	
THREE PLACE DECIMAL: ±		Q.A.	
INTERPRET GEOMETRIC TOLERANCING PER:		COMMENTS:	
MATERIAL			
NEXT ASSY	USED ON	FINISH	
APPLICATION	DO NOT SCALE DRAWING		

TITLE: PLUG		
SIZE	DWG. NO.	REV
D	BLV238	
SCALE: 1:4	WEIGHT:	SHEET 1 OF 1