



MODLE NO.	BLV359	BOTTOM LOADING VALVE, 6 INCH, PILOT CONTROLLED LOADING, WITH EXTERNAL PNEUMATIC UNLOAD ACTUATOR INTERFACES WITH 6 INCH TMA SUMP FLANGE AT TANK AND 6 INCH VICTAULIC FITTING INLET
	E	ADDS PRIMARY AND SECONDARY PILOTS

EXAMPLE:
 P/N BLV359 = BOTTOM LOADING VALVE, 6 INCH WITH EXTERNAL PNEUMATIC UNLOAD ACTUATOR AND PRIMARY PILOT INCLUDED
 P/N BLV359E = BOTTOM LOADING VALVE, 6 INCH WITH EXTERNAL PNEUMATIC UNLOAD ACTUATOR, PRIMARY AND SECONDARY PILOTS INCLUDED

OPTION	ITEM NO.	PART NO.	DESCRIPTIONS	QTY
E	4	RJ1459	ORIFICE	1
E				-
STD	3	RJ1234	PLUG	1
E	2	RJA1115	PILOT	1
STD	1	RJA1269	BOTTOM LOADING VALVE SUBASSEMBLY	1

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF RAYCON INDUSTRIES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF RAYCON INDUSTRIES IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	RAYCON INDUSTRIES
DIMENSIONS ARE IN INCHES		JW	20/07/28	
TOLERANCES:		DRAWN		TITLE: BOTTOM LOADING VALVE 6 INCH
FRACTIONAL: ±		CHECKED		
ANGULAR: MACH ± BEND ±		ENG APPR.		
TWO PLACE DECIMAL: ±		MFG APPR.		
THREE PLACE DECIMAL: ±		Q.A.		SIZE DWG. NO. D BLV359
INTERPRET GEOMETRIC TOLERANCING PER:		COMMENTS:		
MATERIAL	FINISH	APPLICATION	DO NOT SCALE DRAWING	REV -
NEXT ASSY	USED ON			SCALE: 1:4 WEIGHT: SHEET 1 OF 1